
John Deere 250D and 300D Articulated Dump Truck (SN.609166-626760) Diagnostic Service Manual (TM1160)



Covers: 250D,609166-626760),300D,609166-626760)

Type: Service Manual **Language:** English

Pages: 582 Format: PDF

Features: Bookmarked, searchable, printable **Compatibility:** Windows/Mac/Tablet/Mobile

This service manual contains important information for the maintenance, troubleshooting and servicing of the **John Deere 250D and 300D Articulated Dump Truck (SN.609166-626760) Diagnostic Service Manual (TM1160)**

In this manual you will find detailed specifications, illustrations, schematics, diagrams and step-by-step procedures to properly service and diagnose the machine to the manufacturer's standards.

Contents:

- · General Information
- Specifications
- · Serial Number Location
- Engine Specifications
- · Engine Diagnostics
- Engine Tests and Adjustments
- · Engine Repair
- Power Train
- Transmission
- Axles
- Differential
- PTO
- Hydraulic System
- Electrical System
- · Electrical Tests and Diagnostics
- Wiring Diagram / Schematic
- Ignition and Charging
- Steering
- Brakes
- · Wheels
- · Operator's Platform
- Body Panels
- · Disassembly and Assembly
- Diagnostics, Tests and Adjustments
- Troubleshooting
- · and much more...

Please note this manual is in downloadable PDF format only. If you have any questions about this product or would like to request sample pages, please contact us and reference the product name or SKU.	

- [8] Install ECU and mounting plate as an assembly in controller compartment.
- [9] Install controller access panel.
- [10] Turn battery switch to ON position.
- [11] Turn key switch to ON position.

Chassis Control Unit Remove and Install




LEGEND:

- Cap Screw and Washer Electrical Connectors
- 3 Mounting Plate
- Chassis Control Unit

CCU

- [1] Turn key switch and battery disconnect switch to OFF position.
- [2] Remove controller access panel located under left console.
- [3] Remove cap screw and washer (1). Remove chassis control unit (CCU) (4) and mounting plate (3) as an assembly.
- [4] Disconnect electrical connectors (2).

[5] -



LEGEND:

Mounting Plate
Chassis Control Unit
Cap Screws (2 used)

CCU and Mounting Plate Assembly

Remove cap screws (5) to separate CCU (4) from mounting plate (3).

[6] - Repair or replace as neccessary.



Thank you very much for your reading.

Please click here to get more information.