John Deere 644J (SN.-611231), 724J (SN.-611218) 4WD Loader Service Repair Technical Manual (TM2076)

HPX615E Gator™ Utility Vehicle (SN. 010001-)



JOHN HARE



TECHNICAL MANUAL
HPX615E Gator™ Utility Vehicle (SN. 010001-)

TM150919 01DEC18 (ENGLISH)



John Deere Horicon Works

Covers: 644J,611231),724J,611218)

Type: Service Manual **Language:** English

Pages: 398 **Format:** PDF

Features: Bookmarked, searchable, printable **Compatibility:** Windows/Mac/Tablet/Mobile

This service manual contains important information for the maintenance, troubleshooting and servicing of

the John Deere 644J (SN.-611231), 724J (SN.-611218) 4WD Loader Service Repair Technical Manual (TM2076)

In this manual you will find detailed specifications, illustrations, schematics, diagrams and step-by-step procedures to properly service and diagnose the machine to the manufacturer's standards.

Contents:

- · General Information
- Specifications
- · Serial Number Location
- · Engine Specifications
- · Engine Diagnostics
- Engine Tests and Adjustments
- · Engine Repair
- Power Train
- Transmission
- Axles
- Differential
- PTO
- Hydraulic System
- · Electrical System
- · Electrical Tests and Diagnostics
- Wiring Diagram / Schematic
- Ignition and Charging
- Steering
- Brakes
- · Wheels
- · Operator's Platform
- Body Panels
- · Disassembly and Assembly
- Diagnostics, Tests and Adjustments
- Troubleshooting
- · and much more...

Please note this manual is in downloadable PDF format only. If you have any questions about this product or would like to request sample pages, please contact us and reference the product name or SKU.	


CommandQuad • Transmission - Removal and Installation of Components


A

11. Attach commercially available ring eyelet (A) and attach to suitable hoist.

LX265508-UN:

- 8. Lx265505-UN:. Remove nuts (A) and unfasten the cable from the holders.
- 9. Disengage connecting rod from the bell crank lever of the park lock.





LX265507-UN: Main frame removed for illustration purposes.


NOTE:

Not all screws can be removed. Some remain on the switch cover.




LX265506-UN:

Unfasten the shift cover and take it out upwards.



12. Remove special nuts (A).



LX265509-UN: Special Nuts on Range Transmission



Lx265510-UN:
 Place assembly tool on actuator nut KJD10919 (A) as shown.



Thank you very much for your reading.

Please click here to get more information.