



Operation & Maintenance Manual Cutter Crusher

(30 Cutter Crusher) S/N 991100101 & Above (40 Cutter Crusher) S/N 991300101 & Above





OPERATOR SAFETY WARNINGS




Operator must have instructions before operating th Untrained operators the machine. can cause injury or death.


W-2001-0502



Safety Alert Symbol: This symbol is used for important safety messages. When you see this symbol, follow the safety messages to avoid personal injury or death.




Always install approved lift arm support device when servicing loader when lift arms are raised.



Always use the seat bar and fasten seat belt snugly.

Always keep feet on the pedals when operating loader.



CORRECT

P-90216


B-15864

Never use loader without operator cab with ROPS and FOPS approval.




Do not use loader in atmosphere with explosive dust, gas, or where exhaust can contact flammable

Avoid cutting gas, electric, or other utility lines.



Never demolish load bearing walls. Keep other personnel away from work area.


Always use special applications



Do not undercut machine which can cause machine to fall.


Check rules and regulations at your location.

Operator and bystanders must wear goggles, hard hats, and hearing protection.




Always carry attachment as low as possible.

Do not travel or turn with lift arms



Never leave machine with engine running or with lift arms up. To park, engage parking brake and put attachment on the ground.



Never modify equipment or add attachments not by approved Bobcat Company.

demolish ceilings Never overhead structure.

SAFETY EQUIPMENT

The Bobcat Loader must be equipped with safety items necessary for each job. Ask your dealer about attachments and accessories.

- SEAT BELT: Check belt fasteners and check for damaged webbing or buckle.
 SEAT BAR: When up, it must lock the pedals.
 OPERATOR CAB (ROPS and FOPS): It must be on the loader with all fasteners tight.
 OPERATOR'S HADBOOK: Must be in the cab.
- MACHINE AND ATTACHMENT SAFETY SIGNS (DECALS): Replace if damaged, clean if soiled.
- SPECIAL APPLICATIONS KIT
- GRAB HANDLES: Replace if damaged.
- SAFETY TREADS: Replace if damaged. LIFT ARM SUPPORT DEVICE
- 10. PARKING BRAKE

OSW36-0409



CONTENTS

FOREWORD
SAFETY & TRAINING RESOURCES
OPERATING INSTRUCTIONS23
PREVENTIVE MAINTENANCE95
SPECIFICATIONS
WARRANTY111
ALPHABETICAL INDEX115
REFERENCE INFORMATION
Write the correct information for YOUR Bobcat attachment in the spaces below. Always use these numbers when referring to your Bobcat attachment.
Attachment Serial Number
NOTES:
YOUR BOBCAT DEALER:
ADDRESS:
PHONE:

CE

Bobcat Company P.O. Box 128 Gwinner, ND 58040-0128 UNITED STATES OF AMERICA

Doosan Benelux SA Drève Richelle 167 B-1410 Waterloo BELGIUM



Thank you very much for your reading.

Please click here to get more information.